

Pigtail

[Brand : FLEX-TECH]

Application

LP Gas Hose (Ref Drawing No. D-HA-C.3) is served as LPG-supplied gas systems, operating at pressure of no more than 350 P.S.I.G.

The hose is made of thermoplastic, certified by CSA to CAN 1-8.3-77 and recognized component under UL 569 of which two ends are assembled with ¼"-19 PT male brass connectors, available in any length as to be required.

Features

Designed for use with high pressure LPG up to 350 psi and natural gas up to 5 psi for service temperature between -40°C to 60°C,

FLEX-TECH
HOSE & TUBING, LLC.



****Common Length : 2ft & 3ft**

Back Check Valve

[Brand : SCG]

Application

BLUGAZ check valve 101 is designed for using with LPG supplied gas systems operating at pressure of no more than 45 bar and for the range of working temperature of 20°C to 40°C.

Features

Copper Alloy (Brass) construction
¼"-19 PT Male & ¼"-19 PT Female
22-mm hexagonal wrench pad



****Common Size : 1/4" Female x 1/4" Male**

Compact Coupling

[Brand : SCG]

Application

BLUGAZ compact Coupling 202 is designed for using with compact-type valve to adapt Ø20-mm outlet to 1/8"28 female type brass connection.

ON-OFF mechanism is controlled by its handy knob, made of Polyamide Acetone material.

Its double sealing element is made of NBR O-rings, ideal for -20°C to 50°C working temperature range.

Features

Main body made of Zinc
Ø20-mm inlet connection and 1/8"-28 female outlet connection
Polyamide Acetone ON-OFF knob



****Common Size : 1/8" Male x Ø20mm Female**